



H O L Z
C E R T
A U S T R I A

EC-CERTIFICATE OF CONFORMITY

1359 - CPD - 0012

In compliance with the Directive 89/106/EEC of the Council of European Communities of 21 December 1988 on the approximation of laws, regulations and administrative provisions of the Member States relating to the construction products (Construction Products Directive - CPD), amended by the Directive 93/68/EEC of the Council of European Communities of 22 July 1993, it has been stated that the construction product

KLH-solid wood slabs

corresponding to the product specification listed on the back side

placed on the market by

**KLH Massivholz GmbH
A-8842 Katsch/Mur 202**

and produced in the factory

A-8842 Katsch/Mur 202

is submitted by the manufacturer to a factory production control and to the further testing of samples taken at the factory in accordance with a prescribed test plan and that the notified body - HOLZFORSCHUNG AUSTRIA - has performed the initial type-testing for the relevant characteristics of the product, the initial inspection of the factory and of the factory production control and performs the continuous surveillance, assessment and approval of the factory production control.

This certificate attests that all provisions concerning the attestation of conformity and the performances described in the ETA

ETA-06/0138

were applied and that the product fulfils all the prescribed requirements.

This certificate was first issued on 21.06.2007 and remains valid as long as the conditions laid down in the harmonised technical specification in reference or the manufacturing conditions in the factory or the FPC itself are not modified significantly.

Vienna, 21.06.2007

HOLZCERT AUSTRIA
ZVR-860936522

DI M. Spatt
Authorised Signatory



DI S. Czamutjian
Head of Certification Body

Akkreditierte Zertifizierungsstelle der Österreichischen Gesellschaft für Holzforschung



Product specification
to the EC-CERTIFICATE OF CONFORMITY 1359 - CPD - 0012
dated 21.06.2007

Construction product:

KLH-solid wood slabs

Solid wood slabs to be used as structural elements in building

Structure:	mind. 3-layer layers arranged perpendicular (angle of 90°) standard construction with 3, 5 and 7 layers
Thickness:	57 - 250 mm
Width x length	max. 2,95 x 16,50 m
Classes of utilisation :	1, 2
Wood species:	spruce/fir
Adhesives:	PUR



CPD